

AD ELEV 91 FT

VAR 10° W
TA 7000

APP 126.400
TWR 118.900

TEXTUAL DESCRIPTION	ABBREVIATED DESCRIPTION	Expected Path Terminator Coding	Fly-Over Required
<p>NOTES APLICABLE TO ALL SID:</p> <ul style="list-style-type: none"> - RNAV 1 APPROVAL REQUIRED - REQUIRED GNSS - IAS MAX 250 kt BELOW FL100 			
STAR NINAU 1Q RNAV1 (GNSS)			
<u>NINAU</u> at 2500 ft minimum, 7000 ft maximum. To BA506 at or above 2500 ft.	<u>NINAU</u> [A2500+; A7000-] -BA506 [A2500+]	IF TF	Y -
STAR PINPO 1Q RNAV1 (GNSS)			
<u>PINPO</u> at or above FL85. To BA386. To BA504 at or above 2500 ft.	<u>PINPO</u> [F085+] - BA386 - BA504 [A2500+]	IF TF TF	Y - -
STAR PISPU 1Q RNAV1 (GNSS)			
<u>PISPU</u> at or above FL85. To BA386, turn right. To BA504 at or above 2500 ft.	<u>PISPU</u> [F085+] - BA386 - BA504 [A2500+]	IF TF TF	Y - -
STAR POLMO 1Q RNAV1 (GNSS)			
<u>POLMO</u> at or above FL85. To BA505 at or above 2500 ft.	<u>POLMO</u> [F085+] - BA505 [A2500+]	IF TF	Y -
STAR RAMOL 1Q RNAV1 (GNSS)			
<u>RAMOL</u> at or above FL85. To BA505 at or above 2500 ft.	<u>RAMOL</u> [F085+] - BA505 [A2500+]	IF TF	Y -
STAR SISAU 1Q RNAV1 (GNSS)			
<u>SISAU</u> . To BA362 at 2500 ft minimum, 7000 ft maximum. To BA506 at or above 2500 ft.	<u>SISAU</u> - BA362 [A2500+; A7000-] - BA506 [A2500+]	IF TF TF	Y - -
STAR SNT 1Q RNAV1 (GNSS)			
<u>SNT</u> . To BA369 at 2500 ft minimum, 7000 ft maximum, turn right. To BA372 at 2500 ft minimum, 4000 ft maximum, turn right. To BA506 at or above 2500 ft.	<u>SNT</u> - BA369 [A2500+; A7000-; R]- BA372 [A2500+; A4000-; R] - BA506 [A2500+]	IF TF TF TF	Y - - -