

STANDARD INSTRUMENT ARRIVALS (STAR)

RWY 21

**NOTE APPLICABLE TO ALL STAR:**

- SPEED CONTROL: MAX IAS 250 kt at FL100 or below.
- Minimum altitudes (MNM ALT) are indicated for each leg. Except in case of emergency or loss of communications altitudes to maintain are those assigned by ATC. These must respect the indicated MNM ALT.
- Expect a NDB approach or request a visual contact approach.
- Outside the NDB BVT area of coverage (50 NM from the navaid), follow the magnetic track indicated for each leg instead of the NDB magnetic route.

**DIMKI ONE ROMEO ARRIVAL (DIMKI1R)**

Inbound 208° BVT direct to NDB BVT (IAF).

**NCL TWO ROMEO ARRIVAL (NCL2R)**

Inbound 116° BVT direct to NDB BVT (IAF).

**PINPO ONE ROMEO ARRIVAL (PINPO1R)**

Inbound 220° BVT direct to NDB BVT (IAF).

**SESAT TWO ROMEO ARRIVAL (SESAT2R)**

Inbound 126° BVT direct to NDB BVT (IAF).

**SISTO TWO ROMEO ARRIVAL (SISTO2R)**

Inbound 108° BVT direct to NDB BVT (IAF).

**PRAIA TWO ROMEO ARRIVAL (SNT2R)**

Inbound 034° BVT direct to NDB BVT (IAF).